

Ivosheen

A finishing acrylic paint, formulated to give excellent durability for interior or exterior applications.



UV Resistant:

Has excellent ultra violet resistant properties ensuring extended life.



Stain Resistant:

Non-yellowing and good stain resistance, will not embrittle.



Easy to Maintain:

Very low dirt retention and easy to clean.



Flexible Application:

Suitable for use on most surfaces provided surface preparation is done properly.

Technical Profile

NO. OF COMPONENTS	1
OVERCOAT TIME	6 hours
COVERAGE	10 - 12m ² L
RECOMMENDED NO. OF COATS	Primer + 2 coats dependent on substrate
DRY FILM THICKNESS	40 microns
COLOUR	Various
CLEANER	Water

SPEED OF CURE**	25 °C
Touch Dry	30 min
Service	6 hrs
Full Cure	7 days

**Cure times at temperatures between 0-30 °C can be achieved by altering the quantity of catalyst used. For applications falling outside of this temperature range, please contact your local Flowcrete Technical Department.

Preparation

All surfaces to be clean, sound and dry.
All existing paint surfaces to be thoroughly washed with detergent to remove any dirt.
Stiff bristle or wire brushes used to remove flaking or peeling paint and oxidation products.

Priming - Concrete, Masonry, Plaster & Asbestos

1. Previously coated with good emulsion paints - clean with damp cloth and dry, no priming required.
2. Previously coated with solvent paints - lightly abrade with fine abrasive paper, clean with damp cloth and dry, no priming required.
3. Uncoated - clean with damp cloth, dry, apply one coat of Ivoseal at 6m²/L.

Priming - Galvanized Iron, Aluminium

4. Previously coated and sound - lightly abrade with fine abrasive paper, clean with damp cloth and dry, no priming required.
5. Coated but peeling - remove all paint, wash well with detergent, dry and apply one coat of Ivocryl straw primer at 7m²/L.

Priming - Timber

6. Apply one coat of Ivoseal acrylic at 8m²/L.

Application

7. Apply by brush, mohair roller or airless spray.

Substrate Requirements

Concrete or screed substrate should be a minimum of 25 N/mm², free from laitence, dust and other contamination. Substrate should be dry to 75% RH as per BS8204.

Installation Service

The installation should be carried out by an Approved Flowcrete Applicator. For details of our Approved Applicators, contact your regional Flowcrete office. Detailed application instructions are available upon request.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs and maintenance. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained application teams.

Focus on the Floorzone

Flowcrete is a market leader in specialist industrial and commercial flooring. Systems available include: floor screeds, surface damp proof membranes, decorative flooring, seamless terrazzo, car park deck coatings, tank lining systems... to name just a few. Our objective is to satisfy your Floorzone needs.

Warranty

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages. Please review warranty in detail before installing the products.