



Conrep Bondex

A cementitious polymer modified bonding agent or reinforcement primer.



Corrosion Protection:

Used as corrosion protection for steel reinforcement.



Bond Strength:

Increases bond strength for mortars.



Moisture Barrier:

A good water and chloride barrier.

Technical Profile

NO. OF COMPONENTS	1
MIX RATIO	±5L water / 25kg
YIELD	14L
COVERAGE	±1m ² /L
COLOUR	Grey
SHELF LIFE	6 months
CLEANER	Water

**Cure times at temperatures between 0–30° C can be achieved by altering the quantity of catalyst used. For applications falling outside of this temperature range, please contact your local Flowcrete Technical Department.

Preparation

Surfaces to be clean, sound and free from contaminants. All repair areas should be defined by a 10mm saw cut to avoid feather edging. Pre-soak prepared area with clean water, but avoid ponding. All steel should be sand blasted to remove all contaminants such as rust.

Application

1. Prior to the application of a repair mortar prime with Conrep Bondex.
2. Work in well to ensure complete wetting of concrete.

Substrate Requirements

Concrete or screed substrate should be a minimum of 25 N/mm², free from laitence, dust and other contamination. Substrate should be dry to 75% RH as per BS8204.

Installation Service

The installation should be carried out by an Approved Flowcrete Applicator. For details of our Approved Applicators, contact your regional Flowcrete office. Detailed application instructions are available upon request.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs and maintenance. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained application teams.

Focus on the Floorzone

Flowcrete is a market leader in specialist industrial and commercial flooring. Systems available include: floor screeds, surface damp proof membranes, decorative flooring, seamless terrazzo, car park deck coatings, tank lining systems... to name just a few. Our objective is to satisfy your Floorzone needs.

Warranty

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages. Please review warranty in detail before installing the products.