

## **MATERIAL SAFETY DATA SHEET**

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME** IVORY 312 EPOXY

Road Stud Adhesive

MSDS REVISION NUMBER 0

**MANUFACTURER** Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A epoxy resin blend

UN NUMBER 3082

PREPARED January 2012

-----

SECTION 2 - COMPOSITION

------

**HAZARDOUS COMPONENTS** 1. Bisphenol A type epoxy resin

**R - PHRASES S - PHRASES**R 36 / 38 / 43 / 51 / 53
S - 28 / 37 / 39 / 61

------



-----

**SECTION 3 - HAZARDS IDENTIFICATION** 

**FLAMMABILITY** 4 - Minimal

**HEALTH EFFECTS - EYES** Eye irritant.

**HEALTH EFFECTS - SKIN** Skin irritant.

May cause skin sensitisation.

**HEALTH EFFECTS - INGESTION** Harmful if swallowed.

**HEALTH EFFECTS - INHALATION** Vapours are unlikely due to physical properties.

------

**SECTION 4 - FIRST AID MEASURES** 

------

EYE CONTACT Hold eye lids apart and immediately flush with plenty

of water for at least 15 minutes. Seek medical

attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

**INGESTION** Rinse mouth thoroughly with water. Do not induce

vomiting. Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

------

**SECTION 5 - FIRE FIGHTING MEASURES** 

------

FIRE RATING 4 - Minimal

**EXTINGUISHING MEDIA** Foam

Dry powder Carbon dioxide Water spray jet

**REACTIVITY** 4 - Minimal



\_\_\_\_\_

**SECTION 6 - ACCIDENTAL RELEASE MEASURES** 

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

**ENVIRONMENTAL PRECAUTIONS**Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the inhouse capabilities, call a spill responder immediately.

**SECTION 7 - HANDLING AND STORAGE** 

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

**HANDLING** Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

------

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

**EYE PROTECTION** Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

**SKIN PROTECTION** Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus when

there is inadequate ventilation.

**INGESTION PROTECTION** Wash before eating, drinking or smoking. Observe

the rules of hygiene.



## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL FORM Paste **COLOUR** Off White **ODOUR** Faint epoxy Hq N/A **BOILING POINT** > 200℃ **MELTING POINT** No data **FLASH POINT** > 100℃ 4 - Minimal FLAMMABILITY

**VISCOSITY** 320 – 360 / 0 / 5

SPECIFIC GRAVITY 1.620

**SOLUBILITY IN WATER** Practically insoluble in water.

\_\_\_\_\_

**SECTION 10 - STABILITY AND REACTIVITY** 

**VAPOUR PRESSURE** 

-----

CHEMICAL STABILITY Stable

**CONDITIONS TO AVOID** Excessive heating over long periods of time degrades

No data

the product causing discolouration.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong alkalis Amines

**HAZARDOUS DECOMPOSITION PRODUCTS** In a fire, toxic fumes may be generated.

------

SECTION 11 - TOXICOLOGICAL PROPERTIES

\_\_\_\_\_

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT) Vapours are unlikely due to physical properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may cause

skin sensitisation.

**CARCINOGENICITY** Not a known carcinogen.



**SAFETY (S) PHRASES** 

**SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 **IMO SHIPPING NAME** Environmentally hazardous substance, Liquid, N.O.S. IMO CLASS AND DANGER GROUP Class 9, Danger Group III IMO SUBSIDIARY RISK(S) None SECTION 15 - REGULATORY INFORMATION **RISK (R) PHRASES** R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

S 28 - After contact with skin, wash immediately with

S 37 / 39 - Wear suitable gloves and eye/face

S61 - Avoid release to the environment. Refer to

special instruction / material safety data sheet.

plenty of water and soap.

protection.



accepted for error of omission or the consequences thereof.

SECTION 16 - OTHER INFORMATION	
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfor always seek medical advice.	
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is	

Flowcrete SA (Pty) Ltd is an RPM Company