

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 319 EPOXY

General purpose, structural epoxy adhesive

MSDS REVISION NUMBER 1

MANUFACTURER Ivory Industrials (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A epoxy resin blend

UN NUMBER 3082

PREPARED 07 August 2013

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS

1. Bisphenol A type epoxy resin

2. $C_{12} - C_{14}$ Aliphatic glycidyl ether

R - PHRASES S - PHRASESR 36 / 38 / 43 / 51 / 53
S - 28 / 37 / 39 / 61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 4 - Minimal

HEALTH EFFECTS - EYES Eye irritant.

HEALTH EFFECTS - SKIN Skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTIONHarmful if swallowed.

HEALTH EFFECTS - INHALATION Vapours are unlikely due to physical properties.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with plenty

of water for at least 15 minutes. Seek medical

attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

INGESTION Rinse mouth thoroughly with water. Do not induce

vomiting. Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 4 - Minimal

EXTINGUISHING MEDIA Foam

Dry powder Carbon dioxide Water spray jet

REACTIVITY 4 - Minimal



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONS

Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus when

there is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Paste
COLOUR Paste
Off White

ODOUR

Paint epoxy

PH

N/A

BOILING POINT

No data

FLASH POINT

FLAMMABILITY

OIT Write

Faint epoxy

N/A

> 200 °C

No data

> 100 °C

FLAMMABILITY

4 - Minimal

VAPOUR PRESSURE No data
SPECIFIC GRAVITY 1.33

SOLUBILITY IN WATER Practically insoluble in water.

.....

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Excessive heating over long periods of time

degrades the product causing discolouration.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong alkalis Amines

HAZARDOUS DECOMPOSITION PRODUCTS In a fire, toxic fumes may be generated.

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT)Vapours are unlikely due to physical properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may cause

skin sensitisation.

CARCINOGENICITY Not a known carcinogen.



SECTION 12 - ECOLOGICAL INFORMATION Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. SECTION 13 - DISPOSAL CONSIDERATIONS **WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 **IMO SHIPPING NAME** Environmentally hazardous substance, Liquid, N.O.S. **IMO CLASS AND DANGER GROUP** Class 9, Danger Group III **IMO SUBSIDIARY RISK(S)** None **SECTION 15 - REGULATORY INFORMATION RISK (R) PHRASES** R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. **SAFETY (S) PHRASES** S 28 - After contact with skin, wash immediately with

plenty of water and soap.

protection.

S 37 / 39 - Wear suitable gloves and eye/face

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.



accepted for error of omission or the consequences thereof.

SECTION 16 - OTHER INFORMATION
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is

Flowcrete (SA) Pty Ltd (2003/029560/07)

176 Voortrekker Street Jacobs Durban 4052

Tel: +27 31 461 3411 Fax: +27 31 461 3475

47 Forge Road Spartan Kempton Park Johannesburg 1620

Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 086 583 8358