

## **MATERIAL SAFETY DATA SHEET**

-----

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION** 

**PRODUCT NAME** FLOWCEM VS EPOXY

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete SA (Pty) Ltd

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Epoxy resin

UN NUMBER 3082

PREPARED January 2014

**SECTION 2 - COMPOSITION** 

\_\_\_\_\_

**HAZARDOUS COMPONENTS** 1. Epoxy resin (average molecular weight < 700)

2. Neodecanoic acid glycidyl ester

**R - PHRASES S - PHRASES**R 36 / 38 / 43 / 51 / 53

S 24 / 26 / 28 / 37 / 39 / 61

\_\_\_\_\_



**EXTINGUISHING MEDIA** 

**SECTION 3 - HAZARDS IDENTIFICATION** 4 - Minimal **FLAMMABILITY HEALTH EFFECTS - EYES** Eye irritant. **HEALTH EFFECTS - SKIN** Skin irritant. May cause skin sensitisation. **HEALTH EFFECTS - INGESTION** Harmful if swallowed. **HEALTH EFFECTS - INHALATION** Vapours are unlikely due to physical properties. **SECTION 4 - FIRST AID MEASURES EYE CONTACT** Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. **SKIN CONTACT** Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. Rinse mouth thoroughly with water. Do not induce INGESTION vomiting. Seek medical attention immediately. **INHALATION** Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. **SECTION 5 - FIRE FIGHTING MEASURES FIRE RATING** 4 - Minimal

Carbon dioxide
Water spray or fog

Dry chemical powder

Foam

Sand or earth (for small fires)



SPECIAL FIRE FIGHTING PROCEDURES Fire fighters should wear boots, gloves, long

sleeved overalls and self-contained breathing

apparatus.

**REACTIVITY** 4 – Minimal

\_\_\_\_\_

**SECTION 6 - ACCIDENTAL RELEASE MEASURES** 

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

**ENVIRONMENTAL PRECAUTIONS**Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or

ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill

responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

**HANDLING** Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

.....

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

**EYE PROTECTION** Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

**SKIN PROTECTION** Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

**RESPIRATORY PROTECTION**No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus

when there is inadequate ventilation.

**INGESTION PROTECTION** Wash before eating, drinking or smoking. Observe

the rules of hygiene.



## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

\_\_\_\_\_

PHYSICAL FORM Mobile liquid COLOUR Milky **ODOUR** Faint epoxy pН N/A **BOILING POINT** No data **MELTING POINT** No data **FLASH POINT** > 100℃ **FLAMMABILITY** 4 - Minimal

FLAMMABILITY 4 - Minin
VAPOUR PRESSURE No data
SPECIFIC GRAVITY 1.00

**SOLUBILITY IN WATER** Soluble in water.

\_\_\_\_\_

**SECTION 10 - STABILITY AND REACTIVITY** 

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID None. Stable under recommended storage and

handling conditions.

INCOMPATIBLE MATERIALS Strong oxidising substances

\_\_\_\_\_

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

**ACUTE INHALATION TOXICITY (LC50, RAT)**Vapours are unlikely due to physical properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may

cause skin sensitisation.

**CARCINOGENICITY** Not a known carcinogen.

\_\_\_\_\_\_



**SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause short term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 **IMO SHIPPING NAME** Environmentally hazardous substance, Liquid, N.O.S. **IMO CLASS AND DANGER GROUP** Class 9, Danger Group III IMO SUBSIDIARY RISK(S) None **SECTION 15 - REGULATORY INFORMATION RISK (R) PHRASES** R 36 / 38 – Irritating to eyes and skin. R 43 – May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. SAFETY (S) PHRASES S 24 – Avoid contact with skin. S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28 - After contact with skin, wash immediately

S 37 / 39 - Wear suitable gloves and eye/face

S61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.

with plenty of water and soap.



accepted for error of omission or the consequences thereof.

SECTION 16 - OTHER INFORMATION
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is

Flowcrete (SA) Pty Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1620
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490
Tel: +27 21 385 0653 Fax: 086 583 8358
Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is an RPM Company