

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME FLOWSEAL EPW ACTIVATOR

Water Based Epoxy Enamel

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete S.A. (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Polyamide mixture

UN NUMBER 3082

PREPARED January 2016

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. < 5% Triethylene tetramine

R - PHRASES R 36 / 38 S - PHRASES S 26



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 4 - Minimal

HEALTH EFFECTS - EYESModerate eye irritant.

HEALTH EFFECTS - SKINModerate skin irritant.

HEALTH EFFECTS - INGESTIONHarmful if swallowed.

HEALTH EFFECTS - INHALATIONMild respiratory tract irritant.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT

Hold eye lids apart and immediately flush with

plenty of water for at least 15 minutes. Seek

medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

INGESTION Rinse mouth thoroughly with water. Do not induce

vomiting. Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 4 - Minimal

EXTINGUISHING MEDIA Carbon dioxide

Water

SPECIAL FIRE FIGHTING PROCEDURES Fire fighters should wear boots, gloves, long

sleeved overalls and self-contained breathing

apparatus.

REACTIVITY 4 - Minimal

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1619
Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358 Email: southafrica@flowcrete.com



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONSContain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE

Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION

No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus

when there is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.

Flawerata SA (Ph.) 1+d (2003/029560/07)

Flowcrete SA (Pty) Ltd (2003/029560/07) 176 Voortrekker Street Jacobs Durban 4052 Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park Johannesburg 1619 Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358

Email: southafrica@flowcrete.com



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Mobile liquid
COLOUR Pigmented

ODOUR Ammoniacal Hq 8.0 - 9.0**BOILING POINT** No data **MELTING POINT** No data **FLASH POINT** > 100°C 4 - Minimal **FLAMMABILITY VAPOUR PRESSURE** No data 72 KU / FP **VISCOSITY**

SPECIFIC GRAVITY 1.35

SOLUBILITY IN WATER Soluble in water.

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID None. Stable under recommended storage and

handling conditions.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide

Carbon dioxide

Irritating and toxic fumes at elevated temperatures.

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) > 9 500 mg / kg

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LC50, RAT) Vapours are unlikely due to physical properties.

EYE AND SKIN CONTACTMild eye and skin irritant.

CARCINOGENICITY Not a known carcinogen.

SECTION 12 - ECOLOGICAL INFORMATION

No data

Flowcrete SA (Pty) Ltd (2003/029560/07) 176 Voortrekker Street Jacobs Durban 4052

47 Forge Road Spartan Kempton Park Johannesburg 1619

Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358 Email: southafrica@flowcrete.com



SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Use a reputable waste disposal contractor. Waste

disposal measures must comply with all Local and

National By-laws.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER 3082

IMO SHIPPING NAME Environmentally hazardous substance, Liquid,

N.O.S

IMO CLASS AND DANGER GROUP Class 9, Group III

IMO SUBSIDIARY RISK(S) None

SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES R 36 / 38 – Irritating to eyes and skin.

SAFETY (S) PHRASES S 26 - In case of contact with eyes, rinse

immediately with plenty of water and seek medical

attention.

SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowseal EPW Activator - Page 5 of 5

Email: southafrica@flowcrete.com

