

## **MATERIAL SAFETY DATA SHEET**

------

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION** 

PRODUCT NAME HYDRASEAL DPM ACTIVATOR

MSDS REVISION NUMBER 0

MANUFACTURER Flowcrete S.A. (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Cycloaliphatic polyamine

UN NUMBER 1760

PREPARED 12 May 2012

-----

SECTION 2 - COMPOSITION

**HAZARDOUS COMPONENTS** 1. Nonyl Phenol

2. Aminoethylpiperazine

HAZARD LABELS Corrosive

**R - PHRASES S - PHRASES**R 21 / 22 / 34 / 36 / 38 / 52 / 53

S 1 / 2 / 26 / 28 / 36 / 37 / 39 / 45 / 61

\_\_\_\_\_\_



**SECTION 3 - HAZARDS IDENTIFICATION FLAMMABILITY** 4 - Minimal **HEALTH EFFECTS - EYES** Corrosive to eyes. Can cause irreversible damage. Severe eye irritant. Corrosive to skin. Can cause burns. **HEALTH EFFECTS - SKIN** Severe skin irritant. May cause skin sensitisation. **HEALTH EFFECTS - INGESTION** Harmful if swallowed. **HEALTH EFFECTS - INHALATION** Severe respiratory tract irritant. **SECTION 4 - FIRST AID MEASURES EYE CONTACT** Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. **SKIN CONTACT** Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. **INGESTION** Immediately give plenty of water. Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately. **INHALATION** Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. **SECTION 5 - FIRE FIGHTING MEASURES FIRE RATING** 4 - Minimal PERSONAL PROTECTIVE EQUIPMENT Self-contained breathing apparatus and protective suit. **EXTINGUISHING MEDIA** High volume water jet.



**SECTION 6 - ACCIDENTAL RELEASE MEASURES** 

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

Contain or dyke the entire perimeter of the contaminated area. Ensure that the spilled material **ENVIRONMENTAL PRECAUTIONS** 

does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the contained

spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a

spill responder immediately.

**SECTION 7 - HANDLING AND STORAGE** 

**STORAGE** Keep in cool, dry, ventilated storage and in closed

containers.

**HANDLING** Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

**EYE PROTECTION** Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

Wear suitable breathing apparatus when there is RESPIRATORY PROTECTION

inadequate ventilation.

**INGESTION PROTECTION** Wash before eating, drinking or smoking. Observe the

rules of hygiene.



-----

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL FORM Mobile liquid **COLOUR** Pale yellow **ODOUR** Slight N/A pН **BOILING POINT** > 200℃ **MELTING POINT** No data **FLASH POINT** > 100℃ **FLAMMABILITY** 4 - Minimal **VAPOUR PRESSURE** No data

**VISCOSITY** 60 – 85 s FC4

SPECIFIC GRAVITY 1.00 SOLUBILITY IN WATER Slight

\_\_\_\_\_

**SECTION 10 - STABILITY AND REACTIVITY** 

\_\_\_\_\_

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Excessive heating over long periods of time degrades

the product.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong alkalis

HAZARDOUS DECOMPOSITION PRODUCTS Carbon oxides

Nitrogen oxides

Burning produces obnoxious and toxic fumes.

SECTION 11 - TOXICOLOGICAL PROPERTIES

-----

ACUTE ORAL TOXICITY (LD50, RAT) > 1000 mg / kg

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT) No data

EYE AND SKIN CONTACT Corrosive to eyes and skin. Severe eye and skin

irritant. Repeated exposure may cause skin

sensitisation.

**CARCINOGENICITY** Not a known carcinogen.

------



**SAFETY (S) PHRASES** 

**SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 1760 **IMO SHIPPING NAME** Corrosive liquid, N.O.S. **IMO CLASS AND DANGER GROUP** Class 8, Danger Group III **IMO SUBSIDIARY RISK(S)** None **SECTION 15 - REGULATORY INFORMATION RISK (R) PHRASES** R 21 / 22 - Harmful in contact with skin and if swallowed. R 34 - Causes burns. R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact.

R 52 / 53 - Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

S 1 / 2 - Keep locked up and out of reach of children. S 26 - In case of contact with eyes, rinse immediately

S 28 - After contact with skin, wash immediately with

with plenty of water and seek medical advice.

plenty of water and soap.



S 36 / 37 / 39 - Wear suitable protective clothing, gloves and eye/face protection.

S 45 – In case of accident or if you feel unwell, seek medical advice immediately.

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION	
Alert workers to this hazardous potential and ensure precautions are taken. always seek medical advice.	In cases of any discomfor

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete SA (Pty) Ltd is an RPM Company