

Flowfresh WR (4 to 9mm)

Used for coving and wall rendering, Flowfresh WR is an antimicrobial, chemical resistant polyurethane.



Hygienic:

Contains Polygiene® - an antimicrobial additive that kills up to 99.9% bacteria



Heat Resistance:

Resistant to hot steam cleaning.



Chemical Resistant:

Protects against the majority of acids used in manufacturing processes.



Durable:

Holds its own against impact as well as heavy traffic.



Cream



Yellow Ochre



Sand Yellow



Tomato Red



Signal Grey



Signal Green



Dusty Grey



Light Blue

The applied colours may differ from the examples shown.
For a full colour chart and samples, contact your regional Flowcrete office.

Technical Profile

FIRE RESISTANCE

BS 476-7	Class 2
----------	---------

WATER PERMEABILITY

Karsten Test	Nil (Impermeable)
--------------	-------------------

TEMPERATURE RESISTANCE

Intermittent Spillages	Up to 100°C
Constant Heat	UP to 90°C

ABRASION RESISTANCE

ASTM D4060	Taber Abrader (1kg load using H22 wheels)	25mg loss per 1000 cycles
------------	---	---------------------------

* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.

SPEED OF CURE

	10°C	20°C	30°C
Light Traffic	36 hrs	24 hrs	12 hrs
Full Traffic	72 hrs	48 hrs	24 hrs
Full Chemical Cure	10 days	7 days	6 days

Model Specification

System	Flowfresh WR
Finish	Textured / Smooth
Thickness	4 to 9mm
Colour	See standard colour chart

Preparatory work and application in accordance with manufacturer's instructions.

Products Included in this System

Primer	Flowprime / Flowfresh Primer
Scatter	Scatter 3
Screed	Flowfresh WR

Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm², and maintain a minimum tensile strength of 1.5 MPa, free from laitance, dust and other contamination. The substrate should have a moisture content of no more than 5%.

Installation Service

This installation should be carried out by an Approved Applicator. For details of our Approved Applicators, contact our regional office. Detailed application instructions are available upon request.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs and maintenance. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained application teams.

Focus on the Floorzone

Flowcrete is a market leader in specialist industrial and commercial flooring. Systems available include: floor screeds, surface damp proof membranes, decorative flooring, seamless terrazzo, car park deck coatings, tank lining systems ... to name just a few. Our objective is to satisfy your Floorzone needs.

Polygiene® and HACCP International

Flowfresh flooring systems are antimicrobial to ISO 22196 standard, owing to the inclusion of Polygiene®, an antimicrobial additive incorporated in the formulation. The Flowfresh range of floor systems is HACCP International certified as safe for use in food environments.

Warranty

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard "Warranty, Terms and Conditions of Sale", copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages. Please review warranty in detail before installing the products.