

Galvprep

An acid based detergent with powerful degreasing properties designed to clean and prepare new or old galvanized steel.



Resistant:

Excellent impact resistance.



Flexibility:

Good flexibility allows for different expansion rates between components.



Vertical Applications:

Thyrotrophic for vertical applications.



Adhesion:

Excellent adhesion to mild steel, aluminium and stainless steel.

Technical Profile

KIT SIZE	5L and 25L
PH	<1
SPREAD RATE	±10m²/L
COLOUR	Clear
CLEANER	Water

Preparation

All surfaces to be clean, dry and sound.

Application

- 1. Apply liberally with a bristle brush or scouring pad.
- 2. Thoroughly scrub in a random motion to assist removal of oil and grime.
- 3. Rinse thoroughly with plenty fresh water.
- 4. Check for water break-free surface. If this is not achieved the first time, repeat the cleaning procedure.
- 5. Allow to dry before painting.

Substrate Requirements

Concrete or screed substrate should be a minimum of 25 N/mm², free from laitence, dust and other contamination. Substrate should be dry to 75% RH as per BS8204.

Installation Service

The installation should be carried out by an Approved Flowcrete Applicator. For details of our Approved Applicators, contact your regional Flowcrete office. Detailed application instructions are available upon request.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs and maintenance. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained application teams.

Focus on the Floorzone

Flowcrete is a market leader in specialist industrial and commercial flooring. Systems available include: floor screeds, surface damp proof membranes, decorative flooring, seamless terrazzo, car park deck coatings, tank lining systems... to name just a few. Our objective is to satisfy your Floorzone needs.

Warranty

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages. Please review warranty in detail before installing the products.

[03/04/18]

Email: southafrica@flowcrete.com

www.flowcretesa.co.za