



Concrete Etchant

A concentrated acid with surfactants to assist degreasing.

Typical Properties

It is used for the etching of concrete floors prior to painting or specialised coatings and can also be used for removing unsightly deposits of cement from face bricks and construction machinery.

Operating Conditions

Application:

- Wet surface thoroughly with fresh water prior to acid etching.
- Use 1:2 with water and apply with a brush by working from the bottom upwards. Always add Concrete Etchant to water.
- Leave until effervescence ceases and flush off with a strong jet of water.
- Theoretical coverage: 100m²/25L.

Handling, Safety & Storage

Product is corrosive to skin, eyes and respiratory tract. Flush with copious amounts of water should there be contact. Use of eye protection is strongly advised. Use in well ventilated area, open windows and doors to allow vapour to escape. Store in cool bunded area.

PPE should be a requirement with all chemically formulated products as precaution, respirator, gloves, goggles and apron. Spillages should be flushed away with copious amounts of water.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is, to the best of Flowcrete's knowledge and belief, accurate and reliable as at the date of issue. However no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability.