

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 310 EPOXY

High build epoxy tar

MSDS REVISION NUMBER

MANUFACTURER Flowcrete SA (Pty) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A epoxy resin blend

UN NUMBER 3082

PREPARED January 2014

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. Bisphenol A type epoxy resin

2. $C_{12} - C_{14}$ Aliphatic glycidyl ether

R - PHRASES R 36 / 38 / 43 / 51 / 53 **S - PHRASES S** 28 / 37 / 39 / 61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 4 - Minimal

HEALTH EFFECTS - EYES Eye irritant.

HEALTH EFFECTS - SKIN Skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTION Harmful if swallowed.

HEALTH EFFECTS - INHALATION Vapours are unlikely due to physical properties.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with plenty of

water for at least 15 minutes. Seek medical attention

immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water. Remove

contaminated clothing and shoes. Seek medical attention if

irritation persists.

INGESTION Rinse mouth thoroughly with water. Do not induce

vomiting. Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is laboured,

give assisted respiration. Seek medical attention

immediately.



SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 4 - Minimal

EXTINGUISHING MEDIA Foam

Dry powder Carbon dioxide Water spray jet

REACTIVITY 4 - Minimal

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONS Contain or dyke the entire perimeter of the contaminated

area. Ensure that the spilled material does not enter any

drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the contained

spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or inhale.

When handling, do not eat, drink or smoke.



SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide readily

accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots. Provide

readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus when there

is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe the

rules of hygiene.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Mobile liquid **COLOUR** Colourless **ODOUR** Faint epoxy pН N/A **BOILING POINT** > 200°C **MELTING POINT** No data FLASH POINT > 100°C **FLAMMABILITY** 4 - Minimal VAPOUR PRESSURE No data

VISCOSITY 95 – 105 KU / FP **SPECIFIC GRAVITY** 1.11 – 1.14

SOLUBILITY IN WATER Practically insoluble in water.

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Excessive heating over long periods of time degrades the

product causing discolouration.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong alkalis Amines



IMO SUBSIDIARY RISK(S)

HAZARDOUS DECOMPOSITION PRODUCTS In a fire, toxic fumes may be generated. **SECTION 11 - TOXICOLOGICAL PROPERTIES** ACUTE ORAL TOXICITY (LD50, RAT) No data ACUTE DERMAL TOXICITY (LD50, RABBIT) No data ACUTE INHALATION TOXICITY (LD50, RAT) Vapours are unlikely due to physical properties. EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may cause skin sensitisation. **CARCINOGENICITY** \ Not a known carcinogen. **SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS** WASTE DISPOSAL Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-**SECTION 14 - TRANSPORT INFORMATION** ------**UN NUMBER** 3082 IMO SHIPPING NAME Environmentally hazardous substance, liquid, n.o.s. IMO CLASS AND DANGER GROUP Class 3, Danger Group II/III

None



SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact.

R 51 / 53 - Toxic to aquatic organisms, may cause long

term adverse effects in the aquatic environment.

SAFETY (S) PHRASES S 28 - After contact with skin, wash immediately with

plenty of water and soap.

S 37 / 39 - Wear suitable gloves and eye/face protection.

S61 - Avoid release to the environment. Refer to special

instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete (SA) Pty Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1620
Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 086 583 8358

Email: southafrica@flowcrete.com Flowcrete SA (Pty) Ltd is an RPM Company Page 6 of 6 MSDS - 310 Epoxy

www.flowcretesa.co.za