

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 310LV EPOXY

Epoxy tar screed

MSDS REVISION NUMBER

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A epoxy resin blend

UN NUMBER 3082

PREPARED January 2014

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. Bisphenol A type epoxy resin

2. $C_{12} - C_{14}$ Aliphatic glycidyl ether

R - PHRASES S - PHRASESR 36/38/43/51/53
S - PHRASES

S 28/37/39/61



SECTION 3 - HAZARDS IDENTIFICATION FLAMMABILITY 4 - Minimal **HEALTH EFFECTS - EYES** Eye irritant. **HEALTH EFFECTS - SKIN** Skin irritant. May cause skin sensitisation. **HEALTH EFFECTS - INGESTION** Harmful if swallowed. **HEALTH EFFECTS - INHALATION** Vapours are unlikely due to physical properties. **SECTION 4 - FIRST AID MEASURES EYE CONTACT** Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. SKIN CONTACT Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. **INGESTION** Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately. **INHALATION** Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. **SECTION 5 - FIRE FIGHTING MEASURES** ______ FIRE RATING 4 - Minimal **EXTINGUISHING MEDIA** Foam Dry powder Carbon dioxide Water spray jet REACTIVITY 4 - Minimal

SECTION 6 - ACCIDENTAL RELEASE MEASURES



...........

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONS Contain or dyke the entire perimeter of the contaminated

area. Ensure that the spilled material does not enter any

drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the contained

spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or inhale.

When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide readily

accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots. Provide

readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus when there

is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe the

rules of hygiene.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Mobile liquid **COLOUR** Colourless **ODOUR** Faint epoxy pН N/A **BOILING POINT** > 200°C **MELTING POINT** No data **FLASH POINT** > 100°C **FLAMMABILITY** 4 - Minimal VAPOUR PRESSURE No data

VISCOSITY 95 – 105 KU / FP **SPECIFIC GRAVITY** 1.11 – 1.14

SOLUBILITY IN WATER Practically insoluble in water.

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Excessive heating over long periods of time degrades the

product causing discolouration.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong alkalis Amines

HAZARDOUS DECOMPOSITION PRODUCTS In a fire, toxic fumes may be generated.

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT) Vapours are unlikely due to physical properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may cause skin

sensitisation.

CARCINOGENICITY Not a known carcinogen.



SECTION 12 - ECOLOGICAL INFORMATION Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS** WASTE DISPOSAL Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-**SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 IMO SHIPPING NAME Environmentally hazardous substance, Liquid, N.O.S. IMO CLASS AND DANGER GROUP Class 9, Danger Group III IMO SUBSIDIARY RISK(S) None SECTION 15 - REGULATORY INFORMATION RISK (R) PHRASES R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. SAFETY (S) PHRASES S 28 - After contact with skin, wash immediately with plenty of water and soap. S 37 / 39 - Wear suitable gloves and eye/face protection. S61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.



SECTION 16 - OTHER INFORMATION
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete SA (Pty) Ltd is an RPM Company