

Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier IIN-312-AC Revision Date: 20/09/2021

Product Name: FC 312 ROAD STUD ADHESIVE

ACT

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Hardener for 2 components coatings - Industrial use.

Supersedes Date:

New SDS

1.3 Details of the supplier of the safety data sheet

Importer: Importer

Manufacturer: StonCor Africa (Pty.) Ltd.

8 Cresset Road

Midrand Industrial Park, Chloorkop

P.O. Box 2205 2001, Johannesburg

South Africa

Regulatory / Technical Information:

+27 11 254 5500

Datasheet Produced by: Chonco, Cebolonkosi - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside US)

Giftinformasjonen: +47 22 59 13 00

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 1
Hazardous to the aquatic environment, Chronic, category 2
Carcinogenicity, category 1A
Serious Eye Damage, category 1
Flammable Liquid, category 3
STOT, single exposure, category 1
Skin Irritation, category 2
Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Benzyl alcohol, Diethylenetriamine, quartz (silicon dioxide)

HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
Acute Toxicity, Inhalation, category 1	H330-1	Fatal if inhaled.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
STOT, single exposure, category 1	H370	Causes damage to organs.
Hazardous to the aquatic environment,	H411	Toxic to aquatic life with long lasting effects.
Chronic, category 2		

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P307+311	IF exposed, call a POISON CENTER or doctor/physician.
P308+313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous	ingredients
i iuzui uuu	ingredients

Name According to EEC quartz (silicon dioxide)	EINEC No. 238-878-4	<u>CAS-No.</u> 14808-60-7	<u>%</u> 75-100	Classifications H350-370
Pitch, coal tar, high- temp.	266-028-2	65996-93-2	2.5 - <10	H350
Diethylenetriamine	203-865-4	111-40-0	2.5 - <10	H302-312-314-317-3 30-335
Benzyl alcohol	202-859-9	100-51-6	2.5 - <10	H302-312-319-332
Creosote-oil,- acenaphthene-fraction	292-605-3	90640-84-9	0.1 - <1.0	
Distillates (coal tar), heavy oils	292-607-4	90640-86-1	0.1 - <1.0	

CAS-No.	M-Factors
14808-60-7	0
65996-93-2	0
111-40-0	0
100-51-6	0
90640-84-9	0
90640-86-1	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off with warm water and soap. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Do not ingest. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Highly flammable.

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks. Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep in a dry, cool and well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

Name	CAS-No.	LTEL ppm	<u>s</u>	TEL ppm
quartz (silicon dioxide)	14808-60-7			
Pitch, coal tar, high-temp.	65996-93-2			
Diethylenetriamine	111-40-0			
Benzyl alcohol	100-51-6			
Creosote-oil,-acenaphthene-fraction	90640-84-9			
Distillates (coal tar), heavy oils	90640-86-1			
<u>Name</u>	CAS-No.	OEL Note		
quartz (silicon dioxide)	14808-60-7			
Pitch, coal tar, high-temp.	65996-93-2			
Diethylenetriamine	111-40-0			
Benzyl alcohol	100-51-6			
Creosote-oil,-acenaphthene-fraction	90640-84-9			

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Viscous Liquid

Physical State Liquid

Odor Ammoniacal
Odor threshold Not determined
pH Not determined

Melting point / freezing point (°C)

Not determined

Not determined

Boiling point/range (°C) 156 - 207

Flash Point, (°C) 40

Evaporation rate Not determined Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

limits

Vapour Pressure Not determined
Vapour density Not determined

Relative density 2.

Solubility in / Miscibility with water Insoluble

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity

Not determined

Explosive properties

Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l: Refer to Base SDS

Calculated grams of VOC per liter of coating product as applied. Specific Gravity (g/cm3) 2.033

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks. Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: This product contains one or more carcinogenic substances. See hazard classification

and precautionary statements in Section 2 for further information.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
65996-93-2	Pitch, coal tar, high-temp.	4300 mg/kg, oral, rat		5000 ppm/4 hr, inh, rat	0.000	0.000
111-40-0	Diethylenetriamine	1080 mg/kg, oral, rat	1090 mg/kg	10 mg/L / 1 hour, inh, rat	0.000	0.000
100-51-6	Benzyl alcohol	1230 mg/kg, rat	2000 mg/kg, rabbit	1000 ppm, rat	0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
14808-60-7	quartz (silicon dioxide)	No information	No information	
65996-93-2	Pitch, coal tar, high-temp.	No information	No information	
111-40-0	Diethylenetriamine	780 mg/l	No information	430 mg/l
100-51-6	Benzyl alcohol	230 mg/l	700 mg/l	460 mg/l
90640-84-9	Creosote-oil,-acenaphthene-fraction	No information	No information	
90640-86-1	Distillates (coal tar), heavy oils	No information	No information	

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN 3066

14.2 UN proper shipping name Paint Related Material

Technical name Not applicable

14.3 Transport hazard class(es) 8

Subsidiary shipping hazard Not applicable

14.4 Packing group PG III

14.5 Environmental hazards Not applicable
 14.6 Special precautions for user EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

WGK Class: Not available

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H350 May cause cancer.

H370 Causes damage to organs.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.