

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 317 AR EPOXY

Abrasion resistant wearing compound

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete SA (Pty) Ltd

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Epoxy resin of Bisphenol A,

epichlorohydrin type

UN NUMBER 3082

PREPARED 1 January 2016

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. Bisphenol A

R - PHRASES S - PHRASESR 36/38/43/51/53
S - PHRASES

S 28/37/39/61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY Minimal

HEALTH EFFECTS - EYES Slight eye irritant.

HEALTH EFFECTS - SKINMild skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTION Harmful if swallowed.

HEALTH EFFECTS - INHALATION Vapours are unlikely due to physical

properties.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush

with plenty of water for at least 15 minutes. Seek medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and

water. Remove contaminated clothing and shoes. Seek medical attention if irritation

persists.

INGESTION Rinse mouth thoroughly with water. Do not

induce vomiting. Seek medical attention

immediately.

INHALATION Move to fresh air. If breathing has stopped

or is laboured, give assisted respiration.

Seek medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING Minimal

REACTIVITY Minimal

IVORY 317 EPOXY - Page 2 of 5



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves,

and eye protection.

ENVIRONMENTAL PRECAUTIONSEnsure that the spilled material does not

enter any drains.

SPILL CLEAN-UP PROCEDURE Collect and place the contaminated materials

in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a

spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in

closed containers.

HANDLING Avoid contact with skin and eyes. Do not

ingest or inhale. When handling, do not eat,

drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles.

Provide readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and

boots. Provide readily accessible safety

showers.

RESPIRATORY PROTECTION No respiratory protection is required under

normal conditions.

INGESTION PROTECTION Wash before eating, drinking or smoking.

Observe the rules of hygiene.

IVORY 317 EPOXY - Page 3 of 5

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1619
Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358

Email: southafrica@flowcrete.com



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM

COLOUR Grey **ODOUR** Faint epoxy pН N/A **BOILING POINT** No data MELTING POINT No data FLASH POINT > 100°C **FLAMMABILITY** 4 - Minimal VAPOUR PRESSURE No data SPECIFIC GRAVITY 2.2 SOLUBILITY IN WATER None

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Excessive heating over long periods of time

degrades the product.

INCOMPATIBLE MATERIALS Amines

HAZARDOUS DECOMPOSITION PRODUCTS None

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) > 2000 mg / kg

ACUTE DERMAL TOXICITY (LD50, RABBIT) > 2000 mg / kg

ACUTE INHALATION TOXICITY (LC50, RAT) Vapours are unlikely due to physical

properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure

may cause skin sensitisation.

CARCINOGENICITY Not a known carcinogen.

IVORY 317 EPOXY - Page 4 of 5

Flowcrete SA (Pty) Ltd (2003/029560/07) 176 Voortrekker Street Jacobs Durban 4052 Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park Johannesburg 1619 Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358 Email: southafrica@flowcrete.com



SECTION 12 - ECOLOGICAL INFORMATION

Material is expected to cause long term adverse effects in the aquatic environment.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Use a reputable waste disposal contractor. Waste disposal measures must comply with

all Local and National By-laws.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER 3082

IMO SHIPPING NAME Environmentally hazardous substance,

Liquid, N.O.S.

IMO CLASS AND DANGER GROUP Class 9, Danger Group II/III

IMO SUBSIDIARY RISK(S) None

SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin

contact.

R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the

aquatic environment.

SAFETY (S) PHRASES S 28 - After contact with skin, wash

immediately with plenty of water and soap. S 37 / 39 - Wear suitable gloves and

eye/face protection.

S61 - Avoid release to the environment. Refer to special instruction / material safety

data sheet.



SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort

always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

IVORY 317 EPOXY - Page 5 of 5