



MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

| | |
|--------------------------------------|--|
| PRODUCT NAME | IVORY 318B EPOXY General purpose, thixotropic, laminating epoxy |
| MSDS REVISION NUMBER | 1 |
| MANUFACTURER | Flowcrete SA (Pty.) Ltd. 176 Voortrekker Street Jacobs 4052 |
| TELEPHONE NUMBER | (031) 461 3411 |
| EMERGENCY TELEPHONE NUMBER(S) | Rob Weyers (031) 461 3411 |
| SYNONYMS | None |
| CHEMICAL FAMILY | Bisphenol A epoxy resin blend |
| UN NUMBER | 3082 |
| PREPARED | January 2011 |

SECTION 2 - COMPOSITION

| | |
|-----------------------------|--|
| HAZARDOUS COMPONENTS | 1. Bisphenol A type epoxy resin 2. C ₁₂ – C ₁₄ Aliphatic glycidyl ether |
| R - PHRASES | R 36 / 38 / 43 / 51 / 53 |
| S - PHRASES | S 28 / 37 / 39 / 61 |

SECTION 3 - HAZARDS IDENTIFICATION

| | |
|------------------------------------|--|
| FLAMMABILITY | 4 - Minimal |
| HEALTH EFFECTS - EYES | Eye irritant. |
| HEALTH EFFECTS - SKIN | Skin irritant. May cause skin sensitisation. |
| HEALTH EFFECTS - INGESTION | Harmful if swallowed. |
| HEALTH EFFECTS - INHALATION | Vapours are unlikely due to physical properties. |

SECTION 4 - FIRST AID MEASURES

| | |
|---------------------|--|
| EYE CONTACT | Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. |
| SKIN CONTACT | Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. |
| INGESTION | Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately. |
| INHALATION | Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. |

SECTION 5 - FIRE FIGHTING MEASURES

| | |
|----------------------------|---|
| FIRE RATING | 4 - Minimal |
| EXTINGUISHING MEDIA | Foam Dry powder Carbon dioxide Water spray jet |
| REACTIVITY | 4 – Minimal |



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear long sleeved clothing, boots, gloves, and eye protection.

ENVIRONMENTAL PRECAUTIONS

Contain or dyke the entire perimeter of the contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE

Working from the outer circumference of the contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE

Keep in cool, dry, ventilated storage and in closed containers.

HANDLING

Avoid contact with skin and eyes. Do not ingest or inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION

Wear chemical safety glasses or goggles. Provide readily accessible eye wash stations.

SKIN PROTECTION

Wear long sleeved clothing, gloves, and boots. Provide readily accessible safety showers.

RESPIRATORY PROTECTION

No respiratory protection is required under normal conditions. Wear suitable breathing apparatus when there is inadequate ventilation.

INGESTION PROTECTION

Wash before eating, drinking or smoking. Observe the rules of hygiene.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------|---------------------------------|
| PHYSICAL FORM | Mobile liquid |
| COLOUR | Colourless |
| ODOUR | Faint epoxy |
| pH | N/A |
| BOILING POINT | > 200°C |
| MELTING POINT | No data |
| FLASH POINT | > 100°C |
| FLAMMABILITY | 4 - Minimal |
| VAPOUR PRESSURE | No data |
| VISCOSITY | 2 500 – 3 500 cps |
| SPECIFIC GRAVITY | 1.11 – 1.14 |
| SOLUBILITY IN WATER | Practically insoluble in water. |

SECTION 10 - STABILITY AND REACTIVITY

| | |
|----------------------------------|--|
| CHEMICAL STABILITY | Stable |
| CONDITIONS TO AVOID | Excessive heating over long periods of time degrades the product causing discolouration. |
| INCOMPATIBLE MATERIALS | Strong oxidising substances Strong acids Strong alkalis Amines |
| HAZARDOUS DECOMPOSITION PRODUCTS | In a fire, toxic fumes may be generated. |

SECTION 11 - TOXICOLOGICAL PROPERTIES

| | |
|---------------------------------------|--|
| ACUTE ORAL TOXICITY (LD50, RAT) | No data |
| ACUTE DERMAL TOXICITY (LD50, RABBIT) | No data |
| ACUTE INHALATION TOXICITY (LD50, RAT) | Vapours are unlikely due to physical properties. |
| EYE AND SKIN CONTACT | Eye and skin irritant. Repeated exposure may cause skin sensitisation. |
| CARCINOGENICITY | Not a known carcinogen. |

SECTION 12 - ECOLOGICAL INFORMATION

Material is expected to cause long term adverse effects in the aquatic environment.

This product is not readily biodegradable.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER

3082

IMO SHIPPING NAME

Environmentally hazardous substance, Liquid, N.O.S.

IMO CLASS AND DANGER GROUP

Class 9, Danger Group III

IMO SUBSIDIARY RISK(S)

None

SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES

R 36 / 38 - Irritating to eyes and skin.
R 43 - May cause sensitisation by skin contact.
R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SAFETY (S) PHRASES

S 28 - After contact with skin, wash immediately with plenty of water and soap.
S 37 / 39 - Wear suitable gloves and eye/face protection.
S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.