

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 401 EPOXY

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete SA (Pty) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Hydroxy functional acrylic mixture

UN NUMBER 1866

PREPARED January 2014

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. Xylene

Methyl propasol acetate

R - PHRASESR 10/20/21/22/36/38/43/52/53 **S - PHRASES**R 10/20/21/22/36/38/43/52/53
S 1/2/26/28/36/37/39/45/51/61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 1 - Serious

HEALTH EFFECTS - EYES Severe eye irritant.

HEALTH EFFECTS - SKIN Severe skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTION Harmful if swallowed.

HEALTH EFFECTS - INHALATION Severe respiratory tract irritant.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with

plenty of water for at least 15 minutes. Seek

medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

INGESTION Rinse mouth thoroughly with water. Do not

induce vomiting. Seek medical attention

immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek

medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 1 - Serious

PERSONAL PROTECTIVE EQUIPMENT Self-contained breathing apparatus and

protective suit.

EXTINGUISHING MEDIA Carbon dioxide

Foam Dry powder



SPECIAL FIRE FIGHTING PROCEDURE

Use water to keep exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapours. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear long sleeved clothing, boots, gloves, and eye protection.

ENVIRONMENTAL PRECAUTIONS

Contain or dyke the entire perimeter of the contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE

Working from the outer circumference of the contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder immediately.

.------

SECTION 7 - HANDLING AND STORAGE

STORAGE

Keep in cool, dry, ventilated storage and in closed containers. Store away from all ignition sources. Avoid sparking conditions. Ground all transfer equipment.

HANDLING

Avoid contact with skin and eyes. Do not ingest or inhale. When handling, do not eat, drink or smoke. Ensure adequate ventilation or exhaust ventilation in the working area. Exhaust ventilation is required if the product is sprayed.



SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles.

Provide readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTIONUse in a well ventilated area. Wear suitable

breathing apparatus when there is inadequate

ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking.

Observe the rules of hygiene.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Mobile liquid COLOUR Clear

ODOUR Smell of solvent

pH N/A
BOILING POINT No data
MELTING POINT No data
FLASH POINT < 23 °C
FLAMMABILITY 1 - Serious
VAPOUR PRESSURE No data
SPECIFIC GRAVITY 1.00

SOLUBILITY IN WATER Not soluble in water

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Heat, sparks, flame and build up of static

electricity.



HAZARDOUS DECOMPOSITION PRODUCTS

No hazardous decomposition products expected when stored and handled correctly.

When exposed to high temperatures carbon monoxide, dioxide, smoke and oxides of nitrogen

may be produced.

SECTION 11 - TOXICOLOGICAL PROPERTIES ACUTE ORAL TOXICITY (LD50, RAT) No data **ACUTE DERMAL TOXICITY (LD50, RABBIT)** No data **ACUTE INHALATION TOXICITY (LC50, RAT)** No data **EYE AND SKIN CONTACT** Severe eye and skin irritant. Repeated exposure may cause skin sensitisation. **SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause long term adverse effects in the aquatic environment. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. SECTION 14 - TRANSPORT INFORMATION **UN NUMBER** 1866 **IMO SHIPPING NAME** Resin solution, Flammable, N.O.S. **IMO CLASS AND DANGER GROUP** Class 3, Danger Group III IMO SUBSIDIARY RISK(S) None



SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES

R 10 - Flammable

R 20 / 21 / 22 - Harmful by inhalation, in contact with skin and if swallowed.

R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact. R 52 / 53 - Harmful to aquatic organisms, may cause long term adverse effects in the aquatic

environment.

SAFETY (S) PHRASES

S 1 / 2 - Keep locked up and out of reach of children.

S 24 - Avoid contact with skin.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28 - After contact with skin, wash immediately with plenty of water and soap.

S 36 / 37 / 39 - Wear suitable protective clothing, gloves and eye/face protection.

S 45 - In case of accident or if you feel unwell, seek medical advice immediately.

S 51 - Use only in well ventilated areas.

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete (SA) Pty Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1620
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490
Tel: +27 21 385 0653 Fax: 086 583 8358

Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is an RPM Company