

## MATERIAL SAFETY DATA SHEET

-----

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME** FLOWCOAT UV HB BASE

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(0310 461 3411

SYNONYMS None

CHEMICAL FAMILY Hydroxy functional acrylic mixture

UN NUMBER 1866

PREPARED January 2011

\_\_\_\_\_\_

SECTION 2 - COMPOSITION

**HAZARDOUS COMPONENTS** 1. Xylene

2. Methyl propasol acetate

**R - PHRASES**R 10/20/21/22/36/38/43/52/53 **S - PHRASES**R 10/20/21/22/36/38/43/52/53
S 1/2/26/28/36/37/39/45/51/61

\_\_\_\_\_



**SECTION 3 - HAZARDS IDENTIFICATION FLAMMABILITY** 1 - Serious **HEALTH EFFECTS - EYES** Severe eye irritant. **HEALTH EFFECTS - SKIN** Severe skin irritant. May cause skin sensitisation. Harmful if swallowed. **HEALTH EFFECTS - INHALATION** Severe respiratory tract irritant. **SECTION 4 - FIRST AID MEASURES EYE CONTACT** Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. SKIN CONTACT Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. **INGESTION** Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately. **INHALATION** Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. **SECTION 5 - FIRE FIGHTING MEASURES FIRE RATING** 1 - Serious PERSONAL PROTECTIVE EQUIPMENT

Self-contained breathing apparatus and protective



**EXTINGUISHING MEDIA** Carbon dioxide

Foam Dry powder

SPECIAL FIRE FIGHTING PROCEDURE

Use water to keep exposed containers cool. If a

leak or spill has not ignited, use water spray to disperse the vapours. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking

water supply.

------

**SECTION 6 - ACCIDENTAL RELEASE MEASURES** 

-----

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONS Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

------

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers. Store away from all ignition sources. Avoid sparking conditions. Ground all transfer

equipment.

**HANDLING** Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke. Ensure adequate ventilation or exhaust ventilation in the working area. Exhaust ventilation is required if

the product is sprayed.



SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

**EYE PROTECTION** Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

**SKIN PROTECTION** Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

**RESPIRATORY PROTECTION**Use in a well ventilated area. Wear suitable

breathing apparatus when there is inadequate

ventilation.

**INGESTION PROTECTION** Wash before eating, drinking or smoking. Observe

the rules of hygiene.

-----

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES** 

PHYSICAL FORM Mobile liquid
COLOUR Pigmented
ODOUR Smell of solvent

pH N/A
BOILING POINT No data
MELTING POINT No data
FLASH POINT < 23 °C
FLAMMABILITY 1 - Serious
VAPOUR PRESSURE No data
SPECIFIC GRAVITY 1.20

SOLUBILITY IN WATER Not soluble in water

\_\_\_\_\_

SECTION 10 - STABILITY AND REACTIVITY

------

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID

Heat, sparks, flame and build up of static electricity.

No hazardous decomposition products expected

when stored and handled correctly.

When exposed to high temperatures carbon monoxide, dioxide, smoke and oxides of nitrogen

may be produced.



SECTION 11 - TOXICOLOGICAL PROPERTIES	
ACUTE ORAL TOXICITY (LD50, RAT)	No data
ACUTE DERMAL TOXICITY (LD50, RABBIT)	No data
ACUTE INHALATION TOXICITY (LC50, RAT)	No data
EYE AND SKIN CONTACT	Severe eye and skin irritant. Repeated exposure may cause skin sensitisation.
SECTION 12 - ECOLOGICAL INFORMATION	
Material is expected to cause long term adverse effort	·
SECTION 13 - DISPOSAL CONSIDERATIONS	
WASTE DISPOSAL	Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws.
SECTION 14 - TRANSPORT INFORMATION	
UN NUMBER	1866
IMO SHIPPING NAME	Resin solution, Flammable, N.O.S.
IMO CLASS AND DANGER GROUP	Class 3, Danger Group III
IMO SUBSIDIARY RISK(S)	None



-----

## **SECTION 15 - REGULATORY INFORMATION**

------

**RISK (R) PHRASES** 

R 10 - Flammable

R 20 / 21 / 22 - Harmful by inhalation, in contact with skin and if swallowed.

R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact.

R 52 / 53 - Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

**SAFETY (S) PHRASES** 

S 1 / 2 - Keep locked up and out of reach of children.

S 24 - Avoid contact with skin.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28 - After contact with skin, wash immediately with plenty of water and soap.

S 36 / 37 / 39 - Wear suitable protective clothing, gloves and eye/face protection.

S 45 - In case of accident or if you feel unwell, seek medical advice immediately.

S 51 - Use only in well ventilated areas.

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.

\_\_\_\_\_\_

## **SECTION 16 - OTHER INFORMATION**

Flowcrete SA (Pty) Ltd is an RPM Company

\_\_\_\_\_

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

\_\_\_\_\_\_

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete (SA) Pty Ltd (2003/029560/07)

176 Voortrekker Street Jacobs Durban 4052

Tel: +27 31 461 3411 Fax: +27 31 461 3475

47 Forge Road Spartan Kempton Park Johannesburg 1620

Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 086 583 8358

Email: southafrica@flowcrete.com

Page 6 of 6 MSDS - Flowcoat UV HB Base