

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME FLOWGUARD HB PRIMER ACTIVATOR

MSDS REVISION NUMBER 1

Flowcrete SA (Pty) Ltd **MANUFACTURER**

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Solvent based epoxy mixture

UN NUMBER 1866

PREPARED January 2011

SECTION 2 - COMPOSITION

1. 2. 3. **HAZARDOUS COMPONENTS** Amine adduct

Benzyl Alcohol

Xylene

Isobutyl Alcohol

R-PHRASES R 10 / 20 / 21 / 22 / 34 / 36 / 38 / 43

S - PHRASES S 2/23/24/26/36/37/38/39/45/61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 2 - Moderate

HEALTH EFFECTS - EYES Severe eye irritant.

HEALTH EFFECTS - SKIN Skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTIONHarmful if swallowed.

HEALTH EFFECTS - INHALATIONRespiratory tract irritant.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with

plenty of water for at least 15 minutes. Seek

medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

INGESTION Immediately give plenty of water. Rinse mouth

thoroughly with water. Do not induce vomiting.

Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek

medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 2 - Moderate

PERSONAL PROTECTIVE EQUIPMENT Self-contained breathing apparatus and

protective suit.

EXTINGUISHING MEDIA Water spray

Carbon dioxide

Alcohol resistant foam

Dry powders



SPECIAL FIRE FIGHTING PROCEDURE

Use water to keep exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapours. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and

eye protection.

ENVIRONMENTAL PRECAUTIONS Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or

ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities,

call a spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in

closed containers. Store away from all ignition sources. Avoid sparking conditions. Ground all

transfer equipment.

HANDLING Avoid contact with skin and eyes. Do not ingest

or inhale. When handling, do not eat, drink or

smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTIONWear chemical safety glasses or goggles.
Provide readily accessible eye wash stations.



SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION Use in a well ventilated area. Wear suitable

breathing apparatus when there is inadequate

ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking.

Observe the rules of hygiene.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM
COLOUR
Pale yellow
ODOUR
Amine
pH
BOILING POINT
No data
MELTING POINT
No data
FLASH POINT

Mobile liquid
Pale yellow
Amine
N/A
No data
40 ℃

FLAMMABILITY2 - ModerateVAPOUR PRESSURENo dataVISCOSITY140 - 160 cps

SPECIFIC GRAVITY 0.98 – 1.00

SOLUBILITY IN WATER Not soluble in water

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable under recommended storage and handling

conditions.

CONDITIONS TO AVOID Heat, sparks, flame and build up of static

electricity.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong Alkalis

HAZARDOUS DECOMPOSITION PRODUCTS Carbon dioxide

Carbon monoxide Oxides of nitrogen



SECTION 11 - TOXICOLOGICAL PROPERTIES ACUTE ORAL TOXICITY (LD50, RAT) No data ACUTE DERMAL TOXICITY (LD50, RABBIT) No data **ACUTE INHALATION TOXICITY (LD50, RAT)** No data **EYE AND SKIN CONTACT** Severe eye and skin irritant. Repeated exposure may cause skin sensitisation. CARCINOGENICITY Not a known carcinogen. SECTION 12 - ECOLOGICAL INFORMATION Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS** WASTE DISPOSAL Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 1866 **IMO SHIPPING NAME** Resin solution, Flammable, N.O.S. **IMO CLASS AND DANGER GROUP** Class 3, Danger Group III IMO SUBSIDIARY RISK(S) None



SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES

R 10 - Flammable

R 20 - Harmful by inhalation.

R 21 / 22 - Harmful in contact with skin and if swallowed.

R 34 - Causes burns.

R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact.

SAFETY (S) PHRASES

S 2 - Keep out of reach of children.

S 23 - Do not breathe vapour or spray.

S 24 - Avoid contact with skin.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 38 - In case of insufficient ventilation, wear suitable respiratory equipment. Use only in well ventilated areas.

S 36 / 37 / 39 - Wear suitable protective clothing, gloves and eye/face protection.

S 45 - In case of accident or if you feel unwell, seek medical advice immediately.

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION

Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is an RPM Company

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete (SA) Pty Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1620
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490
Tel: +27 21 385 0653 Fax: 086 583 8358

Page 6 of 6 MSDS - Flowguard HB Primer Act