

MATERIAL SAFETY DATA SHEET

PRODUCT NAME IVORY 317 HI WEAR FAST SET EPOXY Abrasion resistant wearing compound MSDS REVISION NUMBER 0 MANUFACTURER Flowcrete SA (Pty.) Ltd. 176 Voortrekker Street Jacobs 4052 TELEPHONE NUMBER (031) 461 3411 EMERGENCY TELEPHONE NUMBER(S) Rob Weyers (031) 461 3411 SYNONYMS None CHEMICAL FAMILY Epoxy resin of Bisphenol A, epichlorohydrin type UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES S - PHRASES	SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION	
MANUFACTURER Flowcrete SA (Pty.) Ltd. 176 Voortrekker Street Jacobs 4052 TELEPHONE NUMBER (031) 461 3411 EMERGENCY TELEPHONE NUMBER(S) Rob Weyers (031) 461 3411 SYNONYMS None CHEMICAL FAMILY Epoxy resin of Bisphenol A, epichlorohydrin type UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES S - PHRASES S - PHRASES S - 28 / 37 / 39 / 61	PRODUCT NAME	
TELEPHONE NUMBER (031) 461 3411 EMERGENCY TELEPHONE NUMBER(S) Rob Weyers (031) 461 3411 SYNONYMS None CHEMICAL FAMILY Epoxy resin of Bisphenol A, epichlorohydrin type UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES S - PHRASES S - PHRASES S - 28 / 37 / 39 / 61	MSDS REVISION NUMBER	0
EMERGENCY TELEPHONE NUMBER(S) Rob Weyers (031) 461 3411 SYNONYMS None CHEMICAL FAMILY Epoxy resin of Bisphenol A, epichlorohydrin type UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES S - PHRASES S - 28 / 37 / 39 / 61	MANUFACTURER	176 Voortrekker Street Jacobs
SYNONYMS CHEMICAL FAMILY Epoxy resin of Bisphenol A, epichlorohydrin type UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES S - PHRASES S - PHRASES S - 28 / 37 / 39 / 61	TELEPHONE NUMBER	(031) 461 3411
CHEMICAL FAMILY UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES R 36 / 38 / 43 / 51 / 53 S - PHRASES S 28 / 37 / 39 / 61	EMERGENCY TELEPHONE NUMBER(S)	
UN NUMBER 3082 PREPARED January 2016 SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES R 36 / 38 / 43 / 51 / 53 S - PHRASES S 28 / 37 / 39 / 61	SYNONYMS	None
PREPARED January 2016 SECTION 2 - COMPOSITION Insurance of the property of the pr	CHEMICAL FAMILY	Epoxy resin of Bisphenol A, epichlorohydrin type
### SECTION 2 - COMPOSITION HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES R 36 / 38 / 43 / 51 / 53 S - PHRASES S 28 / 37 / 39 / 61	UN NUMBER	3082
HAZARDOUS COMPONENTS 1. Bisphenol A R - PHRASES R 36 / 38 / 43 / 51 / 53 S - PHRASES S 28 / 37 / 39 / 61	PREPARED	January 2016
R - PHRASES R 36 / 38 / 43 / 51 / 53 S - PHRASES S 28 / 37 / 39 / 61		
S - PHRASES S 28 / 37 / 39 / 61	HAZARDOUS COMPONENTS	1. Bisphenol A
	S - PHRASES	S 28 / 37 / 39 / 61
		·

IVORY 317 HI WEAR EPOXY - Page 1 of 6

SECTION 3 - HAZARDS IDENTIFICATION



FLAMMABILITY Minimal **HEALTH EFFECTS - EYES** Slight eye irritant. **HEALTH EFFECTS - SKIN** Mild skin irritant. May cause skin sensitisation. **HEALTH EFFECTS - INGESTION** Harmful if swallowed. Vapours are unlikely due to physical properties. **HEALTH EFFECTS - INHALATION SECTION 4 - FIRST AID MEASURES EYE CONTACT** Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. **SKIN CONTACT** Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. **INGESTION** Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately. **INHALATION** Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. **SECTION 5 - FIRE FIGHTING MEASURES FIRE RATING** Minimal REACTIVITY Minimal IVORY 317 HI WEAR EPOXY - Page 2 of 6

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1619
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfor

SECTION 6 - ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONSEnsure that the spilled material does not enter any

drains

SPILL CLEAN-UP PROCEDURE Collect and place the contaminated materials in an

approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the inhouse capabilities, call a spill responder

immediately.

.....

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.

IVORY 317 HI WEAR EPOXY - Page 3 of 6

Email: southafrica@flowcrete.com



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM **Paste COLOUR** White **ODOUR**

Faint epoxy Ha N/A **BOILING POINT** No data **MELTING POINT** No data **FLASH POINT** > 100°C 4 - Minimal **FLAMMABILITY** No data **VAPOUR PRESSURE**

SPECIFIC GRAVITY 2.2 **SOLUBILITY IN WATER** None

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Excessive heating over long periods of time

degrades the product.

INCOMPATIBLE MATERIALS Amines

HAZARDOUS DECOMPOSITION PRODUCTS None

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) > 2000 mg / kg

ACUTE DERMAL TOXICITY (LD50, RABBIT) > 2000 mg / kg

ACUTE INHALATION TOXICITY (LC50, RAT) Vapours are unlikely due to physical properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may

cause skin sensitisation.

CARCINOGENICITY Not a known carcinogen.

IVORY 317 HI WEAR EPOXY - Page 4 of 6

Email: southafrica@flowcrete.com



SECTION 12 - ECOLOGICAL INFORMATION Material is expected to cause long term adverse effects in the aquatic environment. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 **IMO SHIPPING NAME** Environmentally hazardous substance, N.O.S. **IMO CLASS AND DANGER GROUP** Class 9, Danger Group III **IMO SUBSIDIARY RISK(S)** None **SECTION 15 - REGULATORY INFORMATION RISK (R) PHRASES** R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. **SAFETY (S) PHRASES** S 28 - After contact with skin, wash immediately with plenty of water and soap. S 37 / 39 - Wear suitable gloves and eye/face protection. S61 - Avoid release to the environment. Refer to special instruction / material safety data sheet. ______

IVORY 317 HI WEAR EPOXY – Page 5 of 6 $\,$



SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

IVORY 317 HI WEAR EPOXY - Page 6 of 6