

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION PRODUCT NAME IVORY 348 EPOXY Chemical resistant epoxy mortar **MSDS REVISION NUMBER** 1 MANUFACTURER Flowcrete SA (Pty.) Ltd. 176 Voortrekker Street Jacobs 4052 **TELEPHONE NUMBER** (031) 461 3411 EMERGENCY TELEPHONE NUMBER(S) **Rob Weyers** (031) 461 3411 **SYNONYMS** None **CHEMICAL FAMILY** Bisphenol A epoxy resin blend 3082 **UN NUMBER** PREPARED January 2014 _____ **SECTION 2 - COMPOSITION** _____ HAZARDOUS COMPONENTS 1. Bisphenol A type epoxy resin 2. C₁₂ – C₁₄ Aliphatic glycidyl ether **R - PHRASES** R 36 / 38 / 43 / 51 / 53 S 28 / 37 / 39 / 61 S - PHRASES _____ _____



SECTION 3 - HAZARDS IDENTIFICATION		
FLAMMABILITY	4 - Minimal	
HEALTH EFFECTS - EYES	Eye irritant.	
HEALTH EFFECTS - SKIN	Skin irritant. May cause skin sensitisation.	
HEALTH EFFECTS - INGESTION	Harmful if swallowed.	
HEALTH EFFECTS - INHALATION	Vapours are unlikely due to physical properties.	
SECTION 4 - FIRST AID MEASURES		
EYE CONTACT	Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately.	
SKIN CONTACT	Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists.	
INGESTION	Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately.	
INHALATION	Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately.	
SECTION 5 - FIRE FIGHTING MEASURES		
FIRE RATING	4 - Minimal	
EXTINGUISHING MEDIA	Foam Dry powder Carbon dioxide Water spray jet	
REACTIVITY	4 - Minimal	



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONSWear long sleeved clothing, boots, gloves, and eye
protection.ENVIRONMENTAL PRECAUTIONSContain or dyke the entire perimeter of the
contaminated area. Ensure that the spilled material
does not enter any drains, surface or ground water.SPILL CLEAN-UP PROCEDUREWorking from the outer circumference of the
contained spill area, absorb the product with sand or
sawdust. Collect and place the contaminated
materials in an approved disposal container. Dispose
of contaminants in accordance with the Local and
National By-laws. Should the spill exceed the in-
house capabilities, call a spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE

HANDLING

Keep in cool, dry, ventilated storage and in closed containers.

Avoid contact with skin and eyes. Do not ingest or inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION	Wear chemical safety glasses or goggles. Provide readily accessible eye wash stations.
SKIN PROTECTION	Wear long sleeved clothing, gloves, and boots. Provide readily accessible safety showers.
RESPIRATORY PROTECTION	No respiratory protection is required under normal conditions. Wear suitable breathing apparatus when there is inadequate ventilation.
INGESTION PROTECTION	Wash before eating, drinking or smoking. Observe the rules of hygiene.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM COLOUR ODOUR pH BOILING POINT MELTING POINT FLASH POINT FLAMMABILITY VAPOUR PRESSURE VISCOSITY SPECIFIC GRAVITY SOLUBILITY IN WATER	Mobile liquid Colourless Faint epoxy N/A > 200 $^{\circ}$ C No data > 100 $^{\circ}$ C 4 - Minimal No data 95 - 105 KU / FP 1.11 - 1.14 Practically insoluble in water.	
SECTION 10 - STABILITY AND REACTIVITY		
CHEMICAL STABILITY	Stable	
CONDITIONS TO AVOID	Excessive heating over long periods of time degrades the product causing discolouration.	
INCOMPATIBLE MATERIALS	Strong oxidising substances Strong acids Strong alkalis Amines	
HAZARDOUS DECOMPOSITION PRODUCTS	In a fire, toxic fumes may be generated.	
SECTION 11 - TOXICOLOGICAL PROPERTIES		
ACUTE ORAL TOXICITY (LD50, RAT)	No data	
ACUTE DERMAL TOXICITY (LD50, RABBIT)	No data	
ACUTE INHALATION TOXICITY (LD50, RAT)	Vapours are unlikely due to physical properties.	
EYE AND SKIN CONTACT	Eye and skin irritant. Repeated exposure may cause skin sensitisation.	
CARCINOGENICITY	Not a known carcinogen.	



SECTION 12 - ECOLOGICAL INFORMATION

Material is expected to cause long term adverse effects in the aquatic environment.

This product is not readily biodegradable.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws.

Environmentally hazardous substance, Liquid, N.O.S.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER

IMO SHIPPING NAME

IMO CLASS AND DANGER GROUP

IMO SUBSIDIARY RISK(S)

None

Class 9, Danger Group III

3082

SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES	R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.	
SAFETY (S) PHRASES	 S 28 - After contact with skin, wash immediately with plenty of water and soap. S 37 / 39 - Wear suitable gloves and eye/face protection. S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet. 	



SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete (SA) Pty Ltd (2003/029560/07) 176 Voortrekker Street Jacobs Durban 4052 Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park Johannesburg 1620 Tel: +27 11 394 1980 Fax: +27 11 394 3003 Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490 Tel: +27 21 385 0653 Fax: 086 583 8358 Email: southafrica@flowcrete.com Flowcrete SA (Pty) Ltd is an RPM Company

Page 6 of 6 MSDS - Ivory 348 Epoxy

www.flowcretesa.co.za